

HEATING SBU  
Cooling & Heating Division



# AQUAMATIC™

Oil / Gas Fired Hot Water Generator




Unique design features

- Pre insulated, plug and play unit.
- Compact pre-wired unit, with control panel and pump mounted on it.
- Calorifier, instead of direct mixing tank, ensures instant start up and dispenses with the requirement for softener on primary circuit.
- Easy to operate and maintain.

Applications

- **Hotel & Hospitality** - Hot water for bathing, swimming pool heating.
- **Automobile & Engineering** - Hot water / degreasing baths.
- **Food Processing** - Sterilisation, sanitation, hot wash, hot air generation.




Technical specifications


Description	Unit	AMW 005	AMW 01	AMW 02	AMW 03	AMW 04	AMW 06
Capacity	kcal / hr	50000	100000	200000	300000	400000	600000
Maximum Outlet Temperature	°C	90					
Water Flow Rate	m³ / hr	4	9	12	18	20	30
Temperature Difference (Δt)	°C	13	11	17	17	20	20
Efficiency		As Per BS 845 Part 1 NCV Basis					
Diesel (HSD)	%	93					
Gas (NG / LPG)	%	92.5					
Fuel		HSD / LPG / NG					
Fuel Firing System		Pressure Jet, Mono-Bloc					
Fuel Consumption							
HSD	kg / hr	5.12	10.24	20.48	30.72	40.96	61.44
NG	Nm³ / hr	6.36	12.72	25.44	38.16	50.87	76.31
LPG	Nm³ / hr	2.17	4.33	8.67	13.00	17.34	26.01
Connected Electrical Load							
HSD / NG / LPG	kW	1.53	2.33	3.08	4.95	5.15	7.30
Dimensions & Weight		Without Calorifier					
L x W x H	m	1.07x0.83x0.91	1.13x1.34x1.85	1.22x1.55x1.97	2.24x1.38x2.23	2.45x1.38x2.23	2.81x1.55x2.51
Dry Weight	kg	500	875	899	1500	1500	2270
Dimensions & Weight		With Calorifier					
L x W x H	m	2.08x0.99x1.69	2.12x1.34x1.85	1.55x2.33x1.95	2.25x2.60x2.25	2.25x2.70x2.41	2.81x3.07x2.67
Dry Weight	kg	1175	1550	1900	3100	3100	3566
Chimney Top Diameter	mm	150	150	200	250	300	350

Note: Efficiency is calculated based on NCV of Diesel as 10500 kcal/kg, LPG as 24940 kcal/Nm³ and Natural Gas as 8500 kcal/Nm³. Above mentioned weight and dimensions may vary with actuals. Please refer to offer document for more details.

P & I scheme  
Aquamatic with calorifier



**THERMAX LIMITED**  
Heating SBU, C&H Division  
D-13, M.I.D.C. Industrial Area, R. D. Aga Road  
Chinchwad, Pune - 411019, INDIA  
Tel.: +91 - 20 - 27470436, 27475941/ 42, 66122100  
Fax: +91 - 20 - 27472049  
E-mail: heating.enquiries@thermaxindia.com  
[www.thermaxindia.com](http://www.thermaxindia.com)



**THERMAX**  
SUSTAINABLE SOLUTIONS  
ENERGY & ENVIRONMENT

Boilers & Heaters

Absorption Cooling

Captive Power

Water & Waste Solutions

Air Pollution Control

Chemicals

**REGIONAL OFFICES** ■ New Delhi ■ Mumbai ■ Kolkata ■ Chennai ■ Ahmedabad ■ Bangalore ■ Hyderabad ■ Pune ■ **INTERNATIONAL OFFICES** ■ UK ■ USA ■ UAE ■ Germany ■ Belgium ■ Denmark ■ Russia ■ Saudi Arabia ■ Thailand ■ Malaysia ■ Phillipines ■ China ■ Brazil ■ Peru ■ Chile ■ Bangladesh ■ Sri Lanka ■ Kenya ■ Nigeria ■ Indonesia

In view of our constant endeavor to improve the quality of our products, we reserve the right to alter or change specifications without prior notice. All photographs shown in this publication are representative in purpose and are to be used for reference purpose only. Whilst this information is given in good faith, no warranty or representation is given concerning such information which must not be taken for establishing any contractual or other commitment binding on Thermax Ltd. For actual details and specifications, please refer the Thermax offer document.